


Table : 3**High - Tensile Galvanised Z Purlins**Specification :-

Material Grade = AS 1397-G 450

Galv = Z 275 Galv Coating = 275 g/m²

Thickness = 1.5mm - 3mm



Purlin Size	Designation Size Number	Weight Mass Per Meter	Thickness t	Wed W	Flange 1 A	Flange 2 B	Lip C
mm	mm	kg/m	mm	mm	mm	mm	mm
150 x 65 x 20	Z 15015	3.59	1.5	150	65	61	20
	Z 15019	4.51	1.9	150	65	61	20
	Z 15023	5.65	2.3	150	65	61	20
	Z 15030	7.03	3.0	150	65	61	20
175 x 75 x 20	Z 17519	5.21	1.9	175	75	69	20
	Z 17523	6.29	2.3	175	75	69	20
	Z 17530	8.17	3.0	175	75	69	20
200 x 75 x 20	Z 20019	5.74	1.9	200	79	73	20
	Z 20023	6.83	2.3	200	79	73	20
	Z 20030	8.91	3.0	200	79	73	20
225 x 75 x 20	Z 22519	6.12	1.9	225	79	73	20
	Z 22523	7.40	2.3	225	79	73	20
	Z 22530	9.65	3.0	225	79	73	20
250 x 75 x 25	Z 25019	6.50	1.9	250	79	73	25
	Z 25023	7.85	2.3	250	79	73	25
	Z 25030	10.23	3.0	250	79	73	25
300 x 100 x 25	Z 30023	9.62	2.3	300	100	93	25
	Z 30030	12.53	3.0	300	100	93	25

Available Hole Size :

1) 22 x 18

2) 22 x 14